

SHORTS

WASTE MANAGEMENT | DEMOLITION | PLANT & TOOL HIRE

DOPPSTADT TROMMEL 414-K Technical Specification

The SM 414-K happily accepts waste and raw materials of all types for screening. It is equally suitable for compost, earths, light construction waste, wood, biomass.

Features & Benefits

Discharge Conveyor:

Width (mm): 800
Length (mm): 3000
Belt speed (m/s): 1
Height (mm): 1000-2200

Discharge Conveyor Side:

Width (mm): 600
Length (mm): 3000
Belt speed (m/s): 2.4
Height (mm): 1750

Screen Drum:

Diameter (mm): 1400
Length (mm): 4200
Mesh size (mm): 8 bis 100
Mesh type: square or round
Drum wall thickness (mm): 6 bis 10
Drum speed (min-1): 0-21
Screening area (m²): 15,9

Drive:

Engine Type: Diesel
Marke: Caterpillar C 2.2
Exhaust Level: EUROMOT IIIA
Fuel Tank (l): 100
Torque (Nm): 143

Excavator & Operator also Available



Weight & Dimensions

Chassis: Steel Tracks

Total Weight (kg): 12000

Length (mm): 10600/12400

Width (mm): 5000/6500

Height (mm): 3300/3400

Transport Width (mm): 2500

Transport Height (mm): 3400

Transport Length (mm): 9850/9950

Hire me from
£1450/week
Self-Operated

Plus Fuel &
Transport!